

CP-DPS-PD08V3-12D

8 Channel SMPS Power Supply


- 2+2 Output Terminals for Easy Installation
- Short Circuit, Over Voltage and Over Current Protection
- AC I/P & DC O/P Terminals are Covered for Safety
- Power On Indicator
- Cable Compensation Switch
- Built-in EMI Filter to Nullify Interference
- 100% Full Load Burn-in Test
- Cooling by Free Air Convection
- Shock Proof Plastic Housing
- Wall Mount Option Along with Desktop



About CP PLUS

The brand that is on its way to lead the world when it comes to the security and surveillance industry, CP PLUS, keeps bombarding the market with the most reliable range of products that have been designed carefully and methodically to automate the whole surveillance and security process, no matter how big your premises are.

It was the initiative to help the public in the area where they are the most vulnerable and to empower the sense of safety in our hearts that had conceptualized CP PLUS. And embarking on its mission to make the world a safer and more secure place has taken the brand's journey to unprecedented levels even when compared to international competitors.



CP-DPS-PD08V3-12D

8 Channel SMPS Power Supply

Feature	Specification
Input voltage	200 ~ 240VAC
Input AC Frequency Range	47 ~ 63Hz
Input Current	≤1A/230VAC
Power Cord	2 Pin (L & N)
Standby Power Consumption	≤0.5W
Inrush Current	≤40A@230VAC
Efficiency (Typ.)	85%
Output voltage	12V, Normal Mode
Output Current	5.0A, Normal mode
Output Current range	0~5.0A, Normal Mode
Rated Power	60W, Normal Mode
Ripple & Noise (max.)	≤240mV
Line Regulation	2%
Load Regulation	3%
Power On Indicator	Support
Cable Compensation Switch	Support, 3 Modes (Normal, Long, Ex. Long)
No. of Output Ports	Single Port (2+ve/2-ve Terminals)
Over Voltage Protection	Support
Over Current Protection	Support
Short Circuit Protection	Support
Dielectric Strength (Hi-pot)	3.0KV
Insulation Resistance	100MΩ@500VDC
Surge Immunity	2.0KV
Operating Temperature	-10°C~+45°C
Operating Humidity	20~90% RH Non-condensing

Feature	Specification
Storage Temperature	-20°C~+85°C
Storage Humidity	10~95% RH
Dimension	141.5mm x 102.6mm x 33.2mm
Weight	0.234 kg without Power Cord and Packing Box
Wall Mount	Support

Company Name:

CP PLUS (Aditya Infotech Ltd.)

F-28 Okhla Industrial Area, Phase 1,

New Delhi 110020, INDIA

Contact Mail ID :- customercare@cpplusworld.com